



IMSA TECHNICAL BULLETIN IWSC #17-38

To: All IMSA WeatherTech SportsCar Championship Competitors

From: IMSA Competition

Date: 16 August 2017

Re: 20170827 IWSC VIR: GTLM and GTD Balance of Performance Tables

In accordance with Attachment 2 of the IMSA WeatherTech SportsCar Championship SSR, the following adjustments are made to the indicated cars. The column listed as current is the current specification after the adjustment is applied and thus the required specification for the event. These decisions come into immediate effect and are applicable until further notice.

IMSA has determined the values listed in all tables based upon Manufacturer submitted data and IMSA's data analysis.

GTLM		Vehicles		Mass		Engine			Rear Wing		Fuel					Notes		
Manufacturer		No Fuel/Driver (kg)		Restrictor (mm)			Boost Ratio	Min Angle (deg)	Gurney Minimum Height (mm)	Type	Minimum Lambda	Tank Capacity (L)		Refueling Restrictor (mm)				
		adj	current	qty.	adj.	current								adj	current		adj	current
Event:		20170827 IWSC VIR		Bulletin: TB 17-38			Date: 8/16/2017											
BMW	M6 GTLM	0	1220				See Table	N/A	15.0	E20	0.96	0.0	107.0	-0.5	35.0			
Corvette	C7R GTE	0	1240	2	+0.5	30.6		N/A	10.0	E20	0.88	0.0	90.0	+0.5	32.0			
Ferrari	488 GTE	0	1250				See Table	N/A	10.0	E20	1.10	0.0	87.0	0.0	29.5			
Ford	GT GTE	0	1265				See Table	N/A	15.0	E20	0.90	-3.0	89.0	-0.5	30.0			
Porsche	911 RSR GTE	0	1250	2	0.0	30.9		N/A	10.0	E20	0.89	0.0	94.0	0.0	29.0			

BMW M6 GTLM

Engine Speed	Boost Ratio
[rpm]	
2000	1.536
2500	1.713
3000	1.873
3500	1.954
4000	1.974
4500	2.003
5000	2.003
5250	1.980
5500	1.933
5750	1.883
6000	1.831
6250	1.770
6500	1.706
6750	1.651
7250	1.532
7350	1.000

Ferrari 488 GTE

Engine Speed	Boost Ratio
[rpm]	
2000	1.784
4000	1.784
4800	1.768
5000	1.764
5150	1.761
5300	1.759
5500	1.753
5700	1.742
5950	1.718
6050	1.701
6150	1.680
6300	1.646
6600	1.571
7000	1.473
7500	1.349
7600	1.000

Ford GT GTE

Engine Speed	Boost Ratio
[rpm]	
2000	1.528
4200	1.528
4900	1.527
5100	1.526
5300	1.522
5400	1.517
5500	1.510
5800	1.481
5950	1.460
6050	1.448
6150	1.437
6300	1.421
6600	1.392
7200	1.312
7700	1.251
7800	1.000

GTD	Vehicles		Mass		Engine				Ride Height		Fuel				Notes				
	Manufacturer	Model	No Fuel/Driver (kg)		Restrictor (mm)			Boost Ratio	Maximum RPM		Minimum Ground Clearance (mm)		Type	Minimum Lambda		Tank Capacity (L)		Refueling Restrictor (mm)	
			adj	current	qty.	adj	current		adj	current	adj	current		λ		adj	current	adj	current
Event: 20170827 IWSC VIR		Bulletin: TB 17-38			Date: 8/16/2017														
Acura	NSX GT3	0	1300				See Table	0	7500	0	50.0	IMSA 100	0.85	-3.0	104.0	-1.5	33.5		
Aston Martin	V12 Vantage GT3	0	1290	2	0.0	41.5		0	7700	0	50.0	IMSA 100	0.90	0.0	108.0	0.0	35.5		
Audi	R8 LMS GT3	0	1320	2	0.0	40.0		0	8500	0	50.0	IMSA 100	0.91	0.0	94.0	-2.0	29.0		
BMW	M6 GT3	0	1325				See Table	0	7250	0	50.0	IMSA 100	0.92	0.0	107.0	0.0	35.0		
Ferrari	488 GT3	0	1345				See Table	0	7500	0	50.0	IMSA 100	0.92	0.0	95.0	+1.5	27.0		
Lamborghini	Huracan GT3	0	1300	2	0.0	39.0		0	8500	0	50.0	IMSA 100	0.91	0.0	95.0	0.0	28.0		
Lexus	RC F GT3	0	1340	2	0.0	38.0		0	7200	0	50.0	IMSA 100	0.86	0.0	93.0	0.0	28.5		
Mercedes	AMG GT3	0	1390	2	0.0	34.5		0	7900	0	50.0	IMSA 100	0.88	0.0	98.0	0.0	30.5		
Porsche	911 GT3 R	0	1285	2	0.0	40.0		0	9500	0	50.0	IMSA 100	0.88	0.0	91.0	0.0	25.5		

Acura NSX GT3

Engine Speed [rpm]	Boost Ratio
2000	1.765
4000	1.765
4500	1.768
5000	1.815
5500	1.880
6000	1.986
6200	2.015
6300	2.025
6400	2.028
6500	2.026
6600	2.021
6700	2.010
6800	1.993
7000	1.960
7500	1.900
7800	1.000

BMW M6 GT3

Engine Speed [rpm]	Boost Ratio
2000	1.595
3000	1.803
4000	1.960
4500	2.014
4750	2.034
5000	2.054
5250	2.023
5500	1.989
5750	1.933
6000	1.900
6250	1.860
6500	1.829
6750	1.741
7000	1.682
7250	1.608
7550	1.000

Ferrari 488 GT3

Engine Speed [rpm]	Boost Ratio
2000	1.438
4000	1.438
4500	1.494
4750	1.526
5000	1.563
5250	1.604
5500	1.644
5750	1.673
6000	1.683
6250	1.674
6500	1.640
6750	1.596
7000	1.554
7250	1.509
7500	1.468
7800	1.000